

## Time Attendance Terminals

- New friendly UI
- Face /Fingerprint/RF/password verification
- USB disk upgrade firmware
- USB disk export/import user information
- Local device generate Smart Attendance Reports



### Time Attendance Terminals

		ASA2212A	ASA1222E	ASA4214F	ASA6214F
Model					
Access Control Function		Lite	--	Pro	Pro
System	Memory	128M RAM + 32M Flash	8M RAM +8M Flash	512M RAM + 256M Flash	512M RAM + 256M Flash
	LCD	2.8"TFT 320x240	2.4"TFT 320x240	4.3" touch screen 480x272	4.3" touch screen 480x272
	Camera	1.3MP		2.0Mp + 1.3Mp (Infrared)	2.0Mp + 1.3Mp (Infrared)
Capacity	User	1,000	1,000	30,000	30,000
	Face Template	--	--	1,000	3,000
	Fingerprint Template	3,000	2,000	3,000	3,000
	Transaction Logs	150,000	100,000	150,000	150,000
RF Option		13.56MHZ Mifare	--	13.56MHZ Mifare/ 125KHZ EM	13.56MHZ Mifare/ 125KHZ EM
Communication	TCP/IP	√	--	√	√
	Wi-Fi	--	--	802.11 b/n/g	802.11 b/n/g
	RS485	--	--	√	√
	RS232	--	--	√	√
	USB	√	√	√	√
	Wiegand	--	--	Input/Output	Input/Output
Alarm		--	--	Alarm In x2 Alarm Out x2	Alarm In x2 Alarm Out x2
Power Supply		12V 1A	5V 1A (packing in)	12V 2A (packing in)	12V 2A (packing in)
Dimension(W×H×Dmm)		192×160×32	175×120×23	214×122×103	214×122 ×103
Operating Temperature		-5°C~55°C	-5°C~55°C	-5°C~55°C	-5°C~55°C
Platform Software		SmartPSS	--	SmartPSS	SmartPSS