

HS-CL15V/HS-CL17V/HS-CL19V LCD Monitor



TFT LCD

Feature

- High Resolution
- Multi Video Standard (NTSC / PAL / AUTO)
- Multi Language Support
- Fast Response Time
- Brightness 250cd/m
- High Contrast at 450:1
- Key Lock Function
- Scan Mode (LARGE / SMALL)
- Auto Power On: AV1 / AV2 / S-Video / VGA Selectable
- Optional: Rack Mount Type
- 2D Comb Filter / 2D De-interlace



Specification

Model	HS-CL15V	HS-CL17V	HS-CL19V
General			
Front Control	Auto, Menu, Up/Down, Source, Power		
Display Resolution (Dot)	640 x 480 @ 60/72/75 800 x 600 @ 56/60/72/75 1024 x 768 @ 60/70/75	640 x 480 @ 60/72/75 800 x 600 @ 56/60/72/75 1024 x 768 @ 60/70/75 1280 x 1024 @ 60/75	640 x 480 @ 60/72/75 800 x 600 @ 56/60/72/75 1024 x 768 @ 60/70/75 1280 x 1024 @ 60/75
Active Area (mm)	304.128(H) x 228.096(V)	337.92(H) x 270.336(V)	376.32(H) x 301.056(V)
Dot Pitch (mm)	0.297 x 0.297mm	0.264 x 0.264mm	0.294 x 0.294mm
LCD Profile Ratio	4:3		
Display Color	16.2M		
Brightness (Central)	250cd/m ² (*1)	250cd/m ² (*1)	250cd/m ² (*1)
Contrast Ratio	450 :1Typ	500 :1Typ	500 :1Typ
Viewing Angle	130°/100°	160°/160°	160°/160°
Response Time	16ms	12ms	12ms
Input Voltage	100~240V AC 60Hz/ 50Hz		
Input Signal	1Vp-p composite video		
Input Impedance	75 ohm		
Output Impedance	75 ohm		
Operating System			
NTSC	525 lines, 60 fields/ sec.		
PAL	625 lines, 50 fields/ sec.		
Connection			
VGA Input	15 pin D-SUB connector		
Video Input/ Output	BNC x 2/ BNC x 2 Looping Output Auto Termination		
Audio Input/ Output(L/R)	RCA x 2/ RCA x 2		
Y/C Input	4-pin DIN connector x 1		
Speaker	2W + 2W	2W + 2W	2W + 2W
Power Consumption	35W	40W	40W
Weight	N.W./ G.W.: 4.9kg / 6.5kg	N.W./ G.W.: 5.6kg / 7.5kg	N.W./ G.W.: 6.5kg/ 8.3kg
Dimension	390(W)x74.2(D)x354.5(H)mm	390(W)x74.2(D)x354.5(H)mm	425(W)x75.6(D)x396(H)mm
Operating Temperature	-10 to 50°C (14 to 122°F)		
Storage Temperature	-20 to 60°C (-4 to 140°F)		
Certificate	CUL, UL, FCC, CE		

(*1) The brightness spec. 250cd/m² is from panel spec. Design and Specifications are subject to change without notice.

Dimension

