

PIH-262/264

- Special Circuit to Avoid Color Rolling
- 3-Axis Camera Construction
- Optically Perfect Impact and Dust Resistant Polycarbonate Dome Cover
- Screw-on Design Dome Cover
- RCA Video Connector for Easy Adjustment on Site



Color Dome Camera



Dimension Unit : mm



Specifications

		Standard Resolution		High Resolution		
Model	NTSC	PIH-2622N6	PIH-2622N3.6	PIH-2642N6	PIH-2642N3.6	
	PAL	PIH-2622P6	PIH-2622P3.6	PIH-2642P6	PIH-2642P3.6	
Power Input Voltage		DC12V ±10%				
Lens	Focal Length	6.0mm	3.6mm	6.0mm	3.6mm	
	Iris	F1.8	F2.0	F1.8	F2.0	
	Angle of View	H	44.5°	73°	44.5°	73°
		V	33.1°	54.5°	33.1°	54.5°
D	56°	92°	56°	92°		
Pick Up Element		Sony 1/3" Super HAD CCD Sensor				
Effective	NTSC	510(H) x 492(V)		768(H) x 494(V)		
Pixels	PAL	500(H) x 582(V)		752(H) x 582(V)		
Chip Size		5.59mm(H) x 4.68mm(V)				
H / V Sync.	NTSC	15.734KHz / 59.94Hz				
Frequency	PAL	15.625KHz / 50Hz				
Sync. Mode		Internal				
Scanning System		2 : 1 Interlace				
Resolution		380 TV Lines		480 TV Lines		
Min. Illumination		0.2 Lux / F1.8		0.5 Lux / F1.8		
S/N Ratio		More than 50dB (AGC OFF)				
Auto Gain Control		36dB Variable Gain				
White Balance		ATW				
Aperture Gain Correction		Horizontal, Vertical				
Electronic Shutter		1/60(1/50)S ~ 1/100,000S (Auto)				
Back Light Compensation		Auto				
Video Output		CVBS1.0Vp-p, 75Ω				
Gamma Characteristic		γ = 0.45				
Power Consumption		2.2W				
Operating Temperature		-10°C ~ +50°C (14°F ~ 122°F)				
Dimension		Dome : Φ98, Base & Fix Ring : Φ112 x 40.5mm				
Weight		250g				

Design and specifications are subject to change without notice.