

PIH-262X/264X

- 3X High Definition Manual Varifocal Lens
- 3-Axis Camera Construction
- Optically Perfect Impact and Dust Resistant Polycarbonate Dome Cover
- Screw-on Design Dome Cover
- RCA Video Connector for Easy Adjustment on Site



Varifocal Dome Camera



Dimension Unit : mm



Specifications

		Standard Resolution		High Resolution	
Model		PIH-2622XN	PIH-2622XP	PIH-2642XN	PIH-2642XP
System		NTSC	PAL	NTSC	PAL
Power Input Voltage		DC12V ±10%			
Lens	Focal Length	3~9mm			
	Iris	F1.4			
	Angle of View	H	90.2°~ 31.8°		
		V	66.3°~ 23.9°		
D		115.3°~ 39.7°			
Pick Up Element		Sony 1/3" Super HAD CCD Sensor			
Effective Pixels		510(H) x 492(V)	500(H) x 582(V)	768(H) x 494(V)	752(H) x 582(V)
Chip Size		5.59mm(H) x 4.68mm(V)			
H / V Sync. Frequency		15.734KHz / 59.94Hz	15.625KHz / 50Hz	15.734KHz / 59.94Hz	15.625KHz / 50Hz
Sync. Mode		Internal			
Scanning System		2 : 1 Interlace			
Resolution		380 TV Lines		480 TV Lines	
Min. Illumination		0.1 Lux / F1.4		0.18 Lux / F1.4	
S/N Ratio		More than 50dB (AGC OFF)			
Auto Gain Control		36dB Variable Gain			
White Balance		ATW			
Aperture Gain Correction		Horizontal, Vertical			
Back Light Compensation		Auto			
Video Output		CVBS1.0Vp-p, 75Ω			
Gamma Characteristic		γ = 0.45			
Power Consumption		2.2W			
Operating Temperature		-10°C ~ +50°C (14°F ~ 122°F)			
Dimension		Dome : Φ98, Base & Fix Ring : Φ112 x 40.5mm			
Weight		270g			

Design and specifications are subject to change without notice.