



| Модель | QSRV-160402-RH-SAS/SATA | QSRV-161002-RH-SAS/SATA | QSRV-260802-RH-SAS/SATA | QSRV-261202-RH-SATA | QSRV-262502-RH-SAS |
|-------------|---|--------------------------------|--|---|---|
| CPU | 2 * Intel® Xeon® Scalable Processor (max 205W CPU) | | | | |
| HDD | 4x 3.5'/2.5' HDD SAS/SATA 3.0 | 10x 3.5'/2.5' HDD SAS/SATA 3.0 | 8x 3.5'/2.5' + 4x 3.5'/2.5' + 2x 2.5' SATA 3.0 | 12x 3.5'/2.5 + 4x 3.5'/2,5' + 2x 2.5'; 6x 2.5' SATA 3.0 | 25x 2.5' + 4x 3.5' + 2x 2.5'; 6x 2.5' SAS 3.0 |
| Память | 24xDDR4 DIMM ECC Up to 3TB DDR4 2400/2133/1866 (32GB)RDIMM/(64GB)LRDIMM | | | | |
| PCI-E | Standard: 1*16X; optional: 1*16X; | | Standard: 2*16X and 1*8X; optional: 2*16X and 4*8X | | |
| MB chipset | Intel® C621 PCH | | | | |
| RAID | Intel® RSTe Support software RAID 0, 1,5 & 10 | | | | |
| PCI-E M.2 | 1*M.2; size: 2242/2280/22110; protocol: NVMe; lane: x4 | | | | |
| Backplane | 12G SAS Expander (option) | | | | |
| BMC + IPMI | Aspeed AST2400 (4GB DDR4) (1x VGA Connector (rear) + 1x VGA Connector (front))+ IPMI 2.0 with virtual media over LAN and KVM over LAN | | | | |
| Сеть | 2*1000M (a. 2*1GbE, b. 4*1GbE, c. 2*10GbE, d. 4*10GbE, e. 2*40GbE) | | | | |
| USB | 2xUSB 3.0 port front, 2xUSB 3.0 port on backplane | | | | |
| FANS | 5 x 4056 PWM (Hot-swappable Module) | | 4 x 8068 PWM (Hot-swappable Module) | | |
| Питание | 550W (1+1) Platinum (Option: 800W (1+1); 1300W(1+1)) | | | | |
| Размер | 1U (790mm*448mm*44mm(D*W*H)) | | 2U (790mm*448mm*88mm(D*W*H)) | | |
| Вес | 12.4kg / 15.25kg | 12.4kg / 15.25kg | 12.4kg / 15.25kg | 12.4kg / 15.25kg | 14kg / 17kg |
| Температура | Working temperature: 10°C ~ 35°C | | | | |