

Модель	QSRV-130402-RH-SATA	QSRV-130402-RH-SATA-D	QSRV-230802-RH-SAS
CPU	Single Intel® Xeon® Processor E3-1200 V3/V4 series (up to 84W CPU)		
HDD	Up to 4x3.5'/2.5'HDD SATA	Up to 4x3.5'/2.5'HDD SATA	Up to 8x3.5'/2.5'HDD SATA/SAS
HDD OS	2*hot-swap 2.5 (optional)	1*2.5' HDD bay hotswap	1*2.5' HDD bay hotswap
Память	4xDDR3 DIMM slot Up to 32GB ECC DDR3-1600/1333/1066 UDIMM		
PCI-E	1*PCIe 8X (in default)		
MB chipset	Intel PCH Lynx point C222 (C226 is option)		
RAID	Intel® RSTe Support software RAID 0, 1, 5 & 10		
JBOD	NO	NO	YES
BMC	Aspeed AST2400 (1GB DDR3)		
IPMI	Support for Intelligent Platform Management Interface v2.0 IPMI 2.0 with virtual media over LAN and KVM over LAN		
Сеть	2xI210-AT 1GbE LAN controller		
USB	2xUSB2.0, 1*VGA		
SATA DOM	Support SATA DOM power connector		
FANS	Up to 4x12038 PWM fans		
Питание	550W (1+1) Platinum		
Размер	1U (460mm*448mm*43.5mm(D*W*H))		2U (460mm*448mm*88mm(D*W*H))
Вес (NW/GW)	12.4kg / 15.25kg	12.4kg / 15.25kg	12.4kg / 15.25kg
Температура	Working temperature: 10°C ~ 35°C		