

Модель	QSRV-150422-RH-SATA-F	QSRV-151022-RH-SAS-F	QSRV-250822-RH-SATA-F	QSRV-251222-RH-SAS-F	QSRV-251622-RH-SAS-F
CPU	2 * Intel® Xeon® Processor E5-2600 V3/V4 series (max 145W CPU)				
HDD	4x 3.5'/2.5' HDD SATA	10x 3.5'/2.5' HDD SAS/SATA	8x 3.5'/2.5' HDD SATA	12x 3.5'/2.5' HDD SAS	12x 3.5'/2.5' HDD SAS + 4x 3.5'/2.5' HDD BACK SAS
HDD OS	1*Fixed 2.5	NO	1*Fixed 2.5 (2*2.5 H/S)	Option 2*2.5 H/S	1*fixed 2.5
Память	16xDDR4 DIMM ECC Up to 1TB DDR4 2400/2133/1866 (32GB)RDIMM/(64GB)LRDIMM				
PCI-E	1 full-height 16X + 1 half-height 16X		a: 2 full height 16XConfig b: 4*full height 8XConfig c: 1*full height 16X and 2*full height 8X'		1 full-height 16X + 1 half-height 16X
MB chipset	Intel® Wellsburg C612 PCH				
RAID	Intel® RSTe Support software RAID 0, 1,5 & 10				
PCI-E M.2	Support M.2 PCI-E Gen3 X4 1*M.2; size: 2242/2280/22110; protocol: NVMe; lane: x4				
BMC + IPMI	Aspeed AST2400 (2GB DDR3) + IPMI 2.0 with virtual media over LAN and KVM over LAN				
Сеть	Support 4x 1GbE LAN or 2x 10Gb Intel 82599 SFP+ ports				
USB	1xUSB3.0 inbuilt port; 2x USB2.0 port front, 2x USB3.0 port on backplane				
FANS	5 x 4056 PWM		3 x 8038 PWM		4 x 8038 PWM
Питание	770W (1+1) Platinum		550W (1+1) Platinum		770W (1+1) Platinum
Размер	1U (675mm*448mm*44mm(D*W*H))		2U (675mm*448mm*88mm(D*W*H))		
Вес	12.4kg / 15.25kg	12.4kg / 15.25kg	12.4kg / 15.25kg	12.4kg / 15.25kg	14kg / 17kg
Температура	Working temperature: 10°C ~ 35°C				