

Модель	QSRV-331604-RH-SATA-V5	QSRV-332404-RH-SATA-V5	QSRV-432404-RH-SATA-V5	QSRV-433604-RH-SATA-V5
CPU	Single Intel® Xeon® Processor E3-1200 V5/V6 series (up to 84W CPU)			
HDD	Up to 16x 3.5'/2.5' HDD SAS/SATA	Up to 24x 3.5'/2.5' HDD SAS/SATA		Up to 36x 3.5'/2.5' HDD SAS/SATA
HDD OS	2*hot-swap 2.5 (optional)			
Память	4xDDR4 DIMM slot Up to 64GB ECC UDIMM			
PCI-E	2 PCIe 8X	1 PCIe 8X	2 PCIe 8X	
MB chipset	Intel PCH Lynx point C232			
RAID	Intel® RSTe Support software RAID 0, 1, 5 & 10			
PCI-E M.2	1*M.2; size: 2242/2280; protocol: NVMe/SATA; lane: x2			
BMC + IPMI	Aspeed AST2400 (2GB DDR3) + IPMI 2.0 with virtual media over LAN and KVM over LAN			
Сеть	4xI210-AT 1GbE LAN controller			
USB	2xUSB2.0, inbuilt 2xUSB2.0 connector			
SATA DOM	Support SATA DOM power connector			
FANS	Up to 4 x 12038 PWM fans			
Питание	550W (1+1) Platinum-Efficiency redundant power MAID GREEN			800W (1+1) Platinum
Размер	3U (500mm**448mm*177mm (D*W*H))		4U (500mm*448mm*177mm(D*W*H))	
Вес	NW: 18 kg \ GW: 21kg		NW: 21 kg \ GW: 24kg	
Температура	Working temperature: 10°C ~ 35°C			

