

Модель	QSRV-352422-RH-SAS-F	QSRV-452422RH-SAS-F	QSRV-453622-RH-SAS-F
CPU	2 * Intel® Xeon® Processor E5-2600 V3/V4 series (max 145W CPU)		
HDD	16x 3.5'/2.5' HDD SAS + 8x 3.5'/2.5' HDD BACK SAS	24x 3.5'/2.5' HDD SAS	24x 3.5'/2.5' HDD SAS + 12x 3.5'/2.5' HDD BACK SAS
HDD OS	2*Fixed 2.5 (2*2.5 H/S)	Option 2*2.5 H/S	
Память	16xDDR4 DIMM ECC Up to 1TB DDR4 2400/2133/1866 (32GB)RDIMM/(64GB)LRDIMM		
PCI-E	1 full-height 16X AND 1 half-height 16X	a: 2 full height 16XConfig b: 4*full height 8XConfig c: 1*full height 16X and 2*full height 8X	
MB chipset	Intel® Wellsburg C612 PCH		
RAID	Intel® RSTe Support software RAID 0, 1,5 & 10		
PCI-E M.2	Support M.2 PCI-E Gen3 X4 1*M.2; size: 2242/2280/22110; protocol: NVMe; lane: x4		
BMC + IPMI	Aspeed AST2400 (2GB DDR3) + IPMI 2.0 with virtual media over LAN and KVM over LAN		
Сеть	Support 2x1GbE LAN + 2x10Gb Intel 82599 SFP+ ports		
USB	1xUSB3.0 inbuilt port; 2x USB2.0 port front, 2x USB3.0 port on backplane		
FANS	3 x 12038 PWM		8 x 8038 PWM
Питание	770W (1+1) Platinum		800W (1+1) Platinum
Размер	3U (675mm*448mm*132.2mm(D*W*H))		4U (675mm*448mm*177mm(D*W*H))
Вес	23.5kg / 30.2kg		25.25kg / 35.2kg 28kg / 35.8kg
Температура	Working temperature: 10°C ~ 35°C		