BRACKETS

PAN & TILTS

DOMES

TELEMET

VID101R

ACCESSORIES

Video Distribution Amplifier

VIDEO ACCESSORIES : ELECTRONIC ACCESSORIES

DESCRIPTION

Receives video signal and provides multiple outputs, at same amplitude as input.

VID101R operates from 240V AC supply and has 16 x VID101, assembled to fit into a 19" rack.



TECHNICAL INFORMATION

Dimensions Unit Weight 483 X 126 X 134 (INC. BNC's) 3.38Kg

110-240V AC at 40VA @ 50/60 Hz

Power Supply

Video Inputs

Video Outputs

Fuse Rating

Bandwidth Signal to Noise Ratio 1V Peak to Peak nominal (2V max) 75 Ohm Termination, Standard BNC
1V Peak to Peak nminal (2V Max.), 75 Ohm Termination, Standard BNC.
Supply Fuse 3A or Less, Product Protected by 500mA Fuse.
10MHz
>42dB

TECHNICAL IMAGE

\bigcirc	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	
	00	0 0	⊙ ⊙	⊙ ⊙	\odot	⊙ ⊙	⊙ ⊙	⊙ ⊙	⊙ ⊙	\odot	⊙ ⊙	0 0	0 0	⊙ ⊙	0 0	
\Box	\odot	0 0	0 0	⊙ ⊙	0 0	⊙ ⊙	⊙ ⊙	0 0	⊙ ⊙	⊙ ⊙	⊙ ⊙	0 0	⊙ ⊙	⊙ ⊙	⊙ ⊙	

L W H Weight

483 126 134 3.38kg

PRODUCT CODES & VERSIONS

VID101 (1 n 5 Out 230V AC)

DSVID101RUK.I01.PDF, Issue Date 07/02

Copyright © 2002 Bewator Ltd. All rights reserved.



Bewator Limited, Albany Street, Newport, South Wales, NP20 5XW, UK. T: +44 (0)1633 821000 F: +44 (0)1633 850893 E: sales@bewator.co.uk W: www.bewator.co.uk