



## HD500-EM

Access Control

### Heavy-duty proximity reader

---

- Compact proximity reader
- Vandal-proof design
- Reading range of up to 6 cm

The HD500-EM is a compact proximity reader for SiPass access control system. It has been designed for both modern office environments and vulnerable locations that require a higher level of protection. It has a vandal-proof design and is impact- and fire-resistant. It has a reading range of up to 6 cm.

## Technical data

---

<b>HD500-EM</b>	
Card technology	125 kHz EM4102
Card read distance	Up to 6 cm
Interface to controller	BC-Link, Clock&Data or Wiegand
Operating voltage	10.6 to 32 VDC
Current consumption	100 mA
Indicators	3 x LED (red/yellow/green) 1 x Buzzer
Environment	Indoor or outdoor use
Operating temperature	-30 to +50 °C
IP rating	IP65
Housing	Polycarbonate case, fully encapsulated electronics, stainless steel outer frame
Colour	Black/stainless steel
Dimensions (W x H x D)	100 x 128 x 18 mm
Keypad	No
Approval	CE

## Details for ordering

---

Type	Part no	Designation	Weight
HD500-EM	S24246-F3901-A1	Heavy-duty proximity reader	0.35 kg

Issued by  
Bewator AB  
SE-171 24 Solna  
Sweden

[www.sbt.siemens.com](http://www.sbt.siemens.com)

© 2008 Copyright by  
Bewator AB, a Siemens company  
Data and design subject to change without notice.  
Supply subject to availability.

---

Document no. **A6V10081540**  
Edition 04.2008