



PD30-EM SiPass Entro Prox Codoor – Scandinavian

Access Control

-
- **All-in-one-reader**
 - **Integrated electromechanical lock**
 - **Mounted straight onto standard Scandinavian lock case**

Prox Codoor is a system Prox reader for SiPass Entro with an integrated electromechanical lock. It is an "all-in-one reader" and is an efficient way to meet any indoor security needs. Since the reader is mounted straight onto a standard lock case, you do not have to make any cuts in the door other than those required for the cables for power and communication.

PD30-EM is suitable for lock cases with a distance of between 105 mm and 116 mm between the center of the door handle and the center of the lock cylinder. It is designed for use with Scandinavian lock cases.

Technical data

PD30-EM	
Card technology	125 kHz EM4102
Card read distance	Up to 3 cm with passive card
Interface to controller	BC-Link
Operating voltage	8 to 40 VDC 8 to 30 VAC
Current consumption	100 mA
Indicators	3 x LED (red/yellow/green)
Environment	Indoor use only
Operating temperature	0 to +50 °C
IP rating	IP30
Housing	Stainless steel housing with ABS base reader head
Colour	Stainless steel
Dimensions (W x H x D)	64 x 250 x 64 mm
Keypad	No
Approval	CE
Supplied with	Dropbox and a 5 metre cable

Details for ordering

Type	Part no	Designation	Weight
PD30-EM	S24246-F8504-A1	Prox Codoor – Scandinavian	1.0 kg

Issued by
Bewator AB
SE-171 24 Solna
Sweden

www.buildingtechnologies.siemens.com

© 2008 Copyright by
Bewator AB, a Siemens company
Data and design subject to change without notice.
Supply subject to availability.

Document no. **A6V10081522**
Edition 04.2008