



## BC615

Access Control

## Magnetic stripe card reader

- **Compact magnetic card reader**
- **Robust construction for outdoor or indoor use**
- **Built in Clock**

BC615 is a compact, magnetic card reader for one door that is programmable from the keypad. It can be used as part of a SiPass Entro system in conjunction with CR1. It can be mounted either indoors or outdoors and it has a built-in clock to make it easy to change security levels. Access registration and printing are possible. The keypad has background illumination. The blocking function is activated when incorrect codes have been entered three times in a row. For flush mounting, use the BB4 flush mounting unit.

## Technical data

<b>BC615</b>	
Interface	RS-232 (printer or system)
Housing	Cast metal with stainless steel keys and security lock
Colour	Grey
Environment	Indoor or outdoor use (IP54 design). In very exposed locations, use SH4 or SH1 rain cover.
IP rating	IP54
Operating temperature	-30 to +50 °C. At 90% relative air humidity.
Operating voltage	12 to 24 VAC/DC
Current consumption	70 mA
Dimensions (W x D x H)	110 x 160 x 47 mm
Card capacity	1,000
Time schedules	15 (with up to four time zones each)
Time zones	15
Card read distance	N/A
Inputs	Exit button request with delay. Door monitoring. Red LED external control (galvanic insulation), max. 12-30 VDC.
Outputs	Voltage-free relay contacts, max. 2 A, 30 VDC. Open collector for alarm/duress, max. 0.5 A, 30 VDC. Open collector for door alarm max. 0.5 A, 30 VDC. Tamper switch internal/external (normally closed), max. 1 A, 30 VDC.
Serial interfaces	RS232: 9600 bps, no parity, 8 bit, 1 start-bit, 1 stopbit.

## Details for ordering

Type	Part no	Designation	Weight
BC615	S24246-F3600-A1	Magnetic stripe card reader	1.4 kg

Issued by  
Bewator AB  
SE-171 24 Solna  
Sweden

© 2008 Copyright by  
Bewator AB, a Siemens company  
Data and design subject to change without notice.  
Supply subject to availability.

[www.buildingtechnologies.siemens.com](http://www.buildingtechnologies.siemens.com)

Document no. **A6V10081437**  
Edition 04.2008